

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 1 of 14

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)
Product code : 13060
Identification of the product : tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)
CAS No : 75-65-0
EC Index-No. : 603-005-00-1
EC No. : 200-889-7
Synonyms : t-Butyl alcohol, Trimethyl carbinol, tert-Butyl alcohol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3. Details of the supplier of the safety data sheet

Company identification

MOLYCHEM INDIA LLP
Office: Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)
Tel: +91 22 4066 8111, 2205 7772 .
Email : info@molychem.net
Works: Plot No. B/9, Badlapur M.I.D.C.,
OPP.Shobhavat Textile Co., Kulgaon, Badlapur (E),
Dist.-Thane-421 503.

1.4. Emergency telephone number

Emergency number : +91 22 4066 8111 (10:00am - 6:00 pm)

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Acute toxicity (inhalation:dust,mist) H332
Category 4
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 2 of 14

Highly flammable liquid and vapour. Harmful if inhaled. May cause respiratory irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]
Hazard pictograms (CLP)



GHS02 GHS07

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

3. Composition/information on ingredients

3.1. Substances

Name : tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

CAS-No : 75-65-0

3.2. Mixtures

Not applicable

4. First aid measures

4.1. Description of first aid measures

First-aid measures general

: Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Call a poison center or a doctor if you feel unwell

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 3 of 14

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth out with water. If you feel unwell, seek medical advice. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Causes serious eye irritation. Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour

Explosion hazard : May form flammable/explosive vapour-air mixture.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 4 of 14

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/ personal protection"

Emergency procedures : Stop release. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

7. Handling and storage

7.1. Precautions for safe handling

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 5 of 14

Precautions for safe handling

: No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes

Hygiene measures

: Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Storage conditions

: Keep in fireproof place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up

Storage away from

: Open flame. Direct sunlight. Overheating. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition

7.3. Specific end use(s)

No additional information available

8. Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 6 of 14

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Eye protection : Chemical goggles or safety glasses
Hand protection : Wear protective gloves
Skin protection : Wear suitable protective clothing
Respiratory protection : Wear appropriate mask. [In case of inadequate ventilation] wear respiratory protection.
Thermal hazards : No additional information available

8.2.3. Environmental exposure controls

Avoid release to the environment

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid
Appearance : clear liquid
Molecular mass : 74.12 g/mol
Colour : Colourless.
Odour : characteristic odour
Odour threshold : Not available
pH : 7 at 20 °C
Melting point : Not applicable
Freezing point : 23 – 26 °C
Boiling point : 82 – 83 °C
Flash point : 11 °C
Auto-ignition temperature : 480 °C
Decomposition temperature : Not available
Flammability (solid, gas) : Flammable Highly flammable liquid and vapour.
Vapour pressure : 41 hPa at 20 °C
Relative vapour density at 20 °C : 2.55 (Air = 1)
Relative density : Not available
Density : About 0.78 g
Solubility : Water: 1000 g/l at 25 °C - Completely miscible
Partition coefficient n-octanol/water (Log : Not available

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 7 of 14

kow)

Viscosity, kinematic

: 4.295 mm²/s

Viscosity, dynamic

: 3.35 mPa·s at 30 °C

9.2. Other information

No additional information available

10. Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Open flame. Direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------------|---|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Inhalation:dust,mist: Harmful if inhaled. |
| Skin corrosion/irritation | : Not classified |
| Additional information | : Not classified |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause respiratory irritation. |
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 8 of 14

12. Ecological information

12.1. Toxicity

Ecology - general

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute)

Not classified

Hazardous to the aquatic environment, long-term (chronic)

Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

13. Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions

Sewage disposal recommendations

: Disposal must be done according to official regulations.

Product/Packaging disposal recommendations

: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Disposal must be done according to official regulations.

Additional information

: Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container. Do not re-use empty containers.

14. Transport information

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 9 of 14

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR) : UN 1120
UN-No. (IMDG) : UN 1120
UN-No. (IATA) : UN 1120
UN-No. (ADN) : UN 1120
UN-No. (RID) : UN 1120

14.2. UN proper shipping name

Proper Shipping Name (ADR) : BUTANOLS
Proper Shipping Name (IMDG) : BUTANOLS
Proper Shipping Name (IATA) : Butanols
Proper Shipping Name (ADN) : BUTANOLS
Proper Shipping Name (RID) : BUTANOLS
Transport document description (ADR) : UN 1120 BUTANOLS, 3, II, (D/E)
Transport document description (IMDG) : UN 1120 BUTANOLS, 3, II
Transport document description (IATA) : UN 1120 Butanols, 3, II
Transport document description (ADN) : UN 1120 BUTANOLS, 3, II
Transport document description (RID) : UN 1120 BUTANOLS, 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3

IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3

RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3

14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 10 of 14

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 11
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33

Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : B
MFAG-No : 129

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 11 of 14

CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L
Inland waterway transport
Classification code (ADN) : F1
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1
Rail transport
Classification code (RID) : F1
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU-Regulations

EU restriction list (REACH Annex XVII)

| Reference code Applicable on | Reference code Applicable on |
|------------------------------|------------------------------|
| 3(a) | tert-BUTANOL |
| 3(b) | tert-BUTANOL |
| 40 | tert-BUTANOL |

Not listed on REACH Annex XIV (Authorisation List)

Not listed on the REACH Candidate List

Not listed on the PIC list (Regulation EU 649/2012)

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 12 of 14

Not listed on the POP list (Regulation EU 2019/1021)

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases

| Code | Description |
|-------|---|
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

Water hazard class (WGK)

: WGK 1, Slightly hazardous to water
(Classification according to AwSV; ID No. 219).

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance
(12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: The substance is not listed

SZW-lijst van mutagene stoffen

: The substance is not listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: The substance is not listed

SZW-lijst van reprotoxische stoffen –
Vruchtbaarheid

: The substance is not listed

SZW-lijst van reprotoxische stoffen –
Ontwikkeling

: The substance is not listed

Denmark

Classification remarks

: Emergency management guidelines for the storage
of flammable liquids must be followed

Danish National Regulations

: Young people below the age of 18 years are not
allowed to use the product

15.2. Chemical safety assessment

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 13 of 14

No chemical safety assessment has been carried out

16. Other information

| Abbreviations and acronyms | |
|----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand |
| COD | Chemical oxygen demand |
| COD | Chemical oxygen demand |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



tert-BUTANOL 98.5 % LR (2-Methylpropan-2-ol)

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 13060

Page 14 of 14

| | |
|---|--|
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |
| | |
| Full text of H- and EUH-statements | |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Safety Data Sheet (SDS), EU This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered