Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 1 of 9

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: SODIUM (METAL) (Coated with liquid paraffin)

Product code: 18040

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification: MOLYCHEM

Office: 78/80 Babu Genu Road, Souri Bldg., 2nd Floor, Mumbai – 400 002 (INDIA) Tel:

+91 22 4066 8111, 2205 7772 . Fax: +91 22 2203 4442.

Email: info@molychem.net

Works: Plot No. B/9, Badlapur M.I.D.C., OPP. Shobhavat Textile Co.,

Kulgaon, Badlapur (E), Dist.-Thane-421 503.

1.4. Emergency telephone number

Emergency number: +91 22 4066 8111 (10:00am - 6:00 pm)

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification: F; R14/15

R14 C; R34

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards: Skin corrosion - Category 1B - Danger (CLP: Skin Corr. 1B) H314

Physical hazards: Substances and mixtures, which in contact with water, emit

flammable gases - Category 1 - Danger (CLP: Water-react. 1) H260

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s): F: Highly flammable

C : Corrosive





R Phrase(s): R14/15: Reacts violently with water, liberating extremely flammable gases.

R34: Causes burns.

S Phrase(s): S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 2 of 9

S43: In case of fire, use.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible).

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms



Signal words: Danger

Hazard statements: H260: In contact with water releases flammable gases which may ignite spontaneously.

H314 : Causes severe skin burns and eye damage.

Precautionary statements

• **Prevention**: P223: Keep away from any possible contact with water, because of violent reaction

and possible flash fire.

P231+P232: Handle under inert gas. Protect from moisture.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P260: Do not breathe dust, fume, gas, mist, vapours, spray.

P264: Wash thoroughly after handling.

• **Response**: P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P335+P334: Brush off loose particles from skin. Immerse in cool water, wrap in wet bandages.

P370+P378: In case of fire: Use for extinction.

- **Storage**: P402+P404: Store in a dry place. Store in a closed container.
- P405: Store locked up.
- **Disposal considerations**: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- 2.3. Other hazards

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 3 of 9

Other hazards: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation: Preparation.

Substance name Contents CAS No Pentasodium (carboxylatomethyl): ----- 583-61-9

iminobis(ethylenenitrilo) tetraacetate

4. First aid measures

4.1. Description of first aid measures

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor.

Skin contact: Immediately call a POISON CENTER or doctor. Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Brush off loose particles from skin. Immerse in cool water, wrap in wet bandages.

Eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Ingestion: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use: Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed General information: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Foam. Dry powder. Carbon dioxide. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

Do not use extinguishing media containing water.

Surrounding fires: Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Under fire conditions, hazardous fumes will be present. Thermal decomposition generates: Corrosive vapours.

5.3. Advice for fire-fighters

Protection against fire: Do not enter fire area without proper protective equipment, including respiratory protection.

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 4 of 9

Special procedures: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders: Equip cleanup crew with proper protection.

Ventilate area.

Special precautions: Do not allow water (or moist air) contact with this material.

For non-emergency personnel: Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods: On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling: Keep away from any possible contact with water, because of violent reaction and possible flash fire. Handle under inert gas. Protect from moisture. Wash contaminated clothing before reuse. Wash thoroughly after handling. Do not breathe dust, fume, gas, mist, vapours, spray.

Technical protective measures: Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep only in the original container in a cool, well ventilated place. Keep container closed when not in use. Keep away from any possible contact with water, because of violent reaction and possible flash fire. Protect from moisture.

Storage regulation: Comply with applicable regulations.

Storage - away from: Strong bases. Strong acids. Sources of ignition. Direct sunlight. Store in dry protected location to prevent any moisture contact.

7.3. Specific end use(s)

Specific end use(s): None.

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection: Avoid all unnecessary exposure.

Material Safety Data Sheet SODIUM (METAL) (Coated with liquid paraffin) Product Code: 18040 VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01 Page 5 of 9

• **Respiratory protection** : Wear approved mask.

• Hand protection : Wear protective gloves.

- Skin protection : Wear suitable protective clothing.
- Eye protection : Chemical goggles or face shield.
- Others: When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits: No data available.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Solid.

Odour threshold: No data available.

pH value: Not applicable.
Melting point [°C]: 97.8 °C
Decomposition point [°C]: N/A
Critical temperature [°C]: N/A

Auto-ignition temperature [${}^{\circ}$ C] : > 115 0 C

Flammability (solid, gas) : N/A

Flash point [°C]: 82 °C Boiling point [°C]: 883 °C Initial boiling point [°C]: N/A Final boiling point [°C]: N/A

Evaporation rate: N/A

Vapour pressure [20°C] : N/A Vapour pressure mm/Hg : N/A

Vapour density: 0,003 Density [g/cm3]: 0,968

Relative density, gas (air=1) : N/A Relative density, liquid (water=1) : N/A

Solubility in water [% weight]: Decomposes violently

Solubility in water : N/A

Log Pow octanol / water at 20°C : No data available.

Solubility: N/A

Viscosity at 40°C [mm2/s]: N/A

9.2. Other information Explosive properties: N/A

Explosion limits - upper [%]: N/A Explosion limits - lower [%]: N/A Oxidising properties: No data available.

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 6 of 9

10. Stability and reactivity

10.1. Reactivity

Reactivity: Highly reactive material.

10.2. Chemical stability

Chemical stability: Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: In contact with water releases flammable gases which may ignite spontaneously. Reacts violently with water.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Extremely high or low temperatures.

Moisture.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products: Fumes. Carbon monoxide. Carbon dioxide.

Thermal decomposition generates: Corrosive vapours.

11. Toxicological information

11.1. Information on toxicological effects

Toxicity information: The product has been not fully tested. The calculated risk has been done under the requirements of the EU regulations.

Acute toxicity

- Inhalation : Based on available data, the classification criteria are not met.
- **Dermal**: Based on available data, the classification criteria are not met.
- Ingestion: Based on available data, the classification criteria are not met.

Corrosion: Causes severe skin burns and eye damage.

Irritation: Based on available data, the classification criteria are not met.

Sensitization: Based on available data, the classification criteria are not met.

Mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Toxic for reproduction: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not

Aspiration hazard: Based on available data, the classification criteria are not met.

12. Ecological information

12.1. Toxicity

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 7 of 9

Toxicity information: The product has been not fully tested. The calculated risk has been done under the requirements of the EU regulations.

12.2. Persistence - degradability

Persistence - degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Not established.

12.4. Mobility in soil

Mobility in soil: Not established.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions: Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Special precautions: Do not allow water (or moist air) contact with this material.

14. Transport information

14.1. Land transport (ADR-RID) Proper shipping name : SODIUM

UN N°: 1428 H.I. nr: X423 ADR - Class: 4.3

Labelling - Transport: 4.3: Contact with water liberates highly flammable gases.

ADR - Classification code: W2

ADR - Group : I

ADR - Packing instructions: P403

ADR - Limited Quantity: 0

ADR - Tunnel code: B/E: Tank carriage: Passage forbidden through tunnels of category

B, C, D y E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name: SODIUM

UN N°: 1428

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 8 of 9

IMO-IMDG - Class or division: 4.3 : Contact with water liberates highly flammable

gases.

IMO-IMDG - Packing group: I

IMO-IMDG - Packing instructions: P403 IMO-IMDG - Limited quantities: None IMO-IMDG - Marine pollution: No

EMS-Nr : F-G S-N

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name: SODIUM

UN N°: 1428

IATA - Class or division: 4.3: Contact with water liberates highly flammable gases.

IATA - Packing group : I

IATA - Passenger and Cargo Aircraft : NOT ALLOWED

IATA - Cargo only : ALLOWED

- Cargo only - Packing instruction : 487- Cargo only - Maximum Quantity/ : 15 kg

Packing ERG-Nr : 4W

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental: Ensure all national/local regulations are observed. **regulations/legislation specific for the substance or mixture**

REACH Restrictions - Annex XVII: The components of this product are not subject to restrictions.

REACH Authorisation - Annex XIV: The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment: It has not been carried out.

16. Other information

Abbreviations and acronyms: PBT: persistent, bioaccumulative and toxic.

vPvB: very persistent and very bioaccumulative

Sources of key data used: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Further information: None.

Material Safety Data Sheet	MOLYCHEM
SODIUM (METAL) (Coated with liquid paraffin)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 18040	Page 9 of 9

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008 DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document

Prepared by: MOLYCHEM (INDIA)

For questions contact: MOLYCHEM

Office: 78/80 Babu Genu Road, Souri Bldg., 2nd Floor, Mumbai – 400 002 (INDIA)

Tel: +91 22 4066 8111, 2205 7772 . Fax: + 91 22 2203 4442.

Email: info@molychem.net

Works: Plot No. B/9, Badlapur M.I.D.C., OPP. Shobhavat Textile Co.,

Kulgaon, Badlapur (E), Dist.-Thane-421 503

(The statements contained herein are offered for informational purposes only and are based upon technical data that MOLYCHEM believes to be accurate. It is intended for use only by persons having the necessary technical skills and at their own discretion and risk. Since conditions and manner of use are outside our control, we make NO WARRANTY, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE.)