

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 1 of 15

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : XYLENE RECTIFIED (SULPHUR FREE) LR
Product code : 19860
Identification of the product : XYLENE RECTIFIED (SULPHUR FREE) LR
CAS No : 1330-20-7
EC Index-No. : 601-022-00-9
EC No. : 215-535-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3. Details of the supplier of the safety data sheet

Company identification MOLYCHEM INDIA LLP
Office: Maker Tower 'E', 41-A2, 4th Floor,
Above Maker Arcade, Cuffe Parade,
Mumbai 400 005 (INDIA)
Tel: +91 22 4066 8111, 2205 7772 .
Email : info@molychem.net
Works: Plot No. B/9, Badlapur M.I.D.C.,
OPP.Shobhavat Textile Co., Kulgaon, Badlapur (E),
Dist.-Thane-421 503.

1.4. Emergency telephone number

Emergency number : +91 22 4066 8111 (10:00am - 6:00 pm)

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Acute toxicity (dermal), Category 4 H312
Acute toxicity (inhal.), Category 4 H332
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 2 of 15

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02



GHS07

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H312+H332 - Harmful in contact with skin or if inhaled.
H315 - Causes skin irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.
: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P280 - Wear protective clothing, eye protection, face protection, protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P331 - Do NOT induce vomiting.

Precautionary statements (CLP)

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

3. Composition/information on ingredients

3.1. Substances

Name : XYLENE RECTIFIED (SULPHUR FREE) LR
CAS-No : 1330-20-7

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 3 of 15

3.2. Mixtures

Not applicable

4. First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of water/.... Wash contaminated clothing before reuse. Get medical advice/attention. Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. If you feel unwell, seek medical advice. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation. Irritation.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 4 of 15

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.
Unsuitable extinguishing media : Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour
Explosion hazard : May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3 Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment
Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/ personal protection"
Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 5 of 15

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up

: Take up liquid spill into absorbent material. Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Notify authorities if product enters sewers or public waters.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

7. Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Do not breathe vapours. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing.

Hygiene measures

: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 6 of 15

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	: Store in original container. Store in a dry place. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage away from	: Stored away from heat, sparks, open flames, and other ignition sources

7.3. Specific end use(s)

No additional information available

8. Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Eye protection	: Chemical goggles or safety glasses
Hand protection	: Wear protective gloves
Skin protection	: Wear suitable protective clothing
Respiratory protection	: Wear appropriate mask. [In case of inadequate ventilation] wear respiratory protection.
Thermal hazards	: No additional information available

8.2.3. Environmental exposure controls

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 7 of 15

Avoid release to the environment

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear colorless
Molecular mass	: 106.17
Colour	: colorless
Odour	: Sweet
Odour threshold	: 0.2 – 2 ppm
pH	: Neutral
Melting point	: Not applicable
Freezing point	: -47.4 °C
Boiling point	: 137 - 143 °C
Flash point	: 30 °C
Auto-ignition temperature	: 466 °C
Decomposition temperature	: Not available
Flammability (solid, gas)	: Flammable Flammable liquid and vapour.
Vapour pressure	: 8.29 mm Hg at 25 °C
Relative vapour density at 20 °C	: 3.66 (Air=1)
Relative density	: Not available
Density	: 0.865 g/cm ³ at 20 °C
Solubility	: Water: Immiscible
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: 0.879 mm ² /s
Viscosity, dynamic	: 0.76 mPa·s at 25 °C
Explosive properties	: Not available
Oxidising properties	: Not available
Explosive limits	: Not available

9.2. Other information

No additional information available

10. Stability and reactivity

10.1. Reactivity

flammable liquid and vapour.

10.2. Chemical stability

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 8 of 15

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Open flame. Direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin
Acute toxicity (inhalation)	: Harmful if inhaled.
Skin corrosion/irritation	: Causes skin irritation
Additional information	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways

12. Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 9 of 15

Rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

13. Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Disposal must be done according to official regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container. Do not re-use empty containers

14. Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1307
UN-No. (IMDG)	: UN 1307
UN-No. (IATA)	: UN 1307
UN-No. (ADN)	: UN 1307
UN-No. (RID)	: UN 1307

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: XYLENES
Proper Shipping Name (IMDG)	: XYLENES
Proper Shipping Name (IATA)	: XYLENES
Proper Shipping Name (ADN)	: XYLENES

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 10 of 15

Proper Shipping Name (RID) : XYLENES
Transport document description (ADR) : UN 1307 XYLENES, 3, III, (D/E)
Transport document description (IMDG) : UN 1307 XYLENES, 3, III,
Transport document description (IATA) : UN 1307 XYLENES, 3, III,
Transport document description (ADN) : UN 1307 XYLENES, 3, III,
Transport document description (RID) : UN 1307 XYLENES, 3, III,

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3

IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3

RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) :

14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5L
Excepted quantities (ADR) : E1

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 11 of 15

Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T19
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Tunnel restriction code (ADR) : D/E
EAC code : 3YE

Transport by sea

Limited quantities (IMDG) : 5L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Stowage category (IMDG) : A
Flash point (IMDG) : 23°C to 30°C c.c
MFAG-No : 130

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 12 of 15

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19

Portable tank and bulk container : T7

instructions (RID)

Portable tank and bulk container special : TP1

provisions (RID)

Tank codes for RID tanks (RID) :LGBF

Transport category (RID) : 3

Colis express (express parcels) (RID) : CE4

Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU-Regulations

EU restriction list

Reference code	\Applicable on
3(a)	XYLENE RECTIFIED
3(b)	XYLENE RECTIFIED
3(c)	XYLENE RECTIFIED
40	XYLENE RECTIFIED

REACH Annex XIV (Authorisation List)

No listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent) .

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (1005/2009)

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 13 of 15

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK)

: WGK 2, Slightly hazardous to water
(Classification according to AwSV; ID No. 206)

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance
(12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: The substance is not listed

SZW-lijst van mutagene stoffen

: The substance is not listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: The substance is not listed

SZW-lijst van reprotoxische stoffen –

: The substance is not listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen –

: The substance is not listed

Ontwikkeling

Denmark

Danish National Regulations

: Young people below the age of 18 years are not
allowed to use the product Pregnant/breastfeeding

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 14 of 15

women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

16. Other information

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand
COD	Chemical oxygen demand
COD	Chemical oxygen demand
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



XYLENE RECTIFIED (SULPHUR FREE) LR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 19860

Page 15 of 15

ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Safety Data Sheet (SDS), EU This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered