iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol) Product Code: 22393 WERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01 Page 1 of 10

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)

Product code: 22393

Identification of the product: Iso butanol

CAS No: 78-83-1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification: MOLYCHEM

Office: 78/80 Babu Genu Road, Souri Bldg., 2nd Floor, Mumbai – 400 002 (INDIA) Tel:

+91 22 4066 8111, 2205 7772 . Fax: +91 22 2203 4442.

Email: info@molychem.net

Works: Plot No. B/9, Badlapur M.I.D.C., OPP. Shobhavat Textile Co.,

Kulgaon, Badlapur (E), Dist.-Thane-421 503.

1.4. Emergency telephone number

Emergency number: +91 22 4066 8111 (10:00am - 6:00 pm).

2. Hazards identification -DSD

2.1. Classification of the substance or mixture

Classification EC 67/548 or EC 1999/45

Classification: R10

R67

Xi; R37/38-41

Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)

Health hazards: Specific Target Organ Toxicity - Single exposure - Respiratory tract

irritation - Category 3 - Warning (CLP: STOT SE 3) H335

Specific Target Organ Toxicity - Single exposure - Narcotic effects - Category 3 -

Warning (CLP: STOT SE 3) H336

Serious eye damage - Category 1 - Danger (CLP: Eye Dam. 1) H318

Skin irritation - Category 2 - Warning (CLP: Skin Corr. 2) H315

Physical hazards: Flammable liquids - Category 3 - Warning (CLP: Flam. Liq. 3) H226

2.2. Label elements

Labelling EC 67/548 or EC 1999/45

Symbol(s) : Xi : Irritant



R Phrase(s): R10: Flammable.

iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol) Product Code: 22393 WERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01 Page 2 of 10

R37/38: Irritating to respiratory system and skin.

R41: Risk of serious damage to eyes.

R67: Vapours may cause drowsiness and dizziness. **S Phrase(s)**: S2: Keep out of the reach of children.

S7/9: Keep container tightly closed and in well-ventilated place.

S13: Keep away from food, drink and animal feeding stuffs.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39: Wear suitable gloves and eye/face protection.

S46: If swallowed seek medical advice immediately and show this container or label.

Labelling Regulation EC 1272/2008 (CLP)

Hazard pictograms







Signal words: Danger

Hazard statements: H226: Flammable liquid and vapour.

H318: Causes serious eye damage.

H315: Causes skin irritation.

H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

Precautionary statements

• General: P102: Keep out of reach of children.

P103: Read label before use.

P101: If medical advice is needed, have product container or label at hand.

• Prevention: P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, lighting, ..., equipment.

P210: Keep away from heat, sparks, open flames or hot surfaces. – No smoking.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust, fume, gas, mist, vapours, spray.

P233: Keep container tightly closed.

P264: Wash thoroughly after handling.

• Response: P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 3 of 10

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P370+P378: In case of fire: Use for extinction.

• Storage: P403+P233: Store in well-ventilated place. Keep container tightly closed.

P403+P235: Store in well-ventilated place. Keep cool.

P405: Store locked up.

• **Disposal considerations**: P501: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

3. Composition/information on ingredients

Substance / Preparation: Isobutanol

CAS No: 78-83-1

Substance name Contents CAS No Isobutanol: 100 % 78-83-1

Substance.

Contains no other components or impurities which will influence the classification of the product.

4. First aid measures

4.1. Description of first aid measures

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin contact: Specific treatment (see on this label). Get medical advice. If skin irritation occurs: Wash contaminated clothing before reuse. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.

Eye contact: Immediately call a POISON CENTER or doctor. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.

Ingestion: Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms relating to use: Causes serious eye damage.

Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 4 of 10

General information: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media: Do not use a heavy water stream.

Surrounding fires: Use water spray or fog for cooling exposed containers.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: Under fire conditions, hazardous fumes will be present.

5.3. Advice for fire-fighters

Protection against fire: Do not enter fire area without proper protective equipment, including respiratory protection.

Special procedures: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water toenter environment.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For emergency responders: Equip cleanup crew with proper protection.

Ventilate area. Avoid breathing dust, fume, gas, mist, vapours, spray.

Technical measures: Use special care to avoid static electric charges.

Special precautions: Remove ignition sources. No naked lights. No smoking.

For non-emergency personnel: Evacuate unnecessary personnel.

6.2. Environmental precautions

Environmental precautions: Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean up methods: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See section 8. Exposure controls/personal protection

7. Handling and storage

7.1. Precautions for safe handling

Handling: Handle empty containers with care because residual vapours are flammable. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Take precautionary measures against static discharge.

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 5 of 10

Technical protective measures: Provide good ventilation in process area to prevent formation of vapour. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical, ventilating, lighting, ..., equipment. Use only non sparking tools.

Special precautions: No naked lights. No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

7.2. Conditions for safe storage, including any incompatibilities

Storage: Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Ground/bond container and receiving equipment. Keep container tightly closed.

Storage - away from: Strong bases. Strong acids. Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s) Specific end use(s): None.

8. Exposure controls/personal protection

8.1. Exposure controls

Personal protection: Avoid all unnecessary exposure.

- **Respiratory protection**: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Hand protection : Wear protective gloves.
- Skin protection : Wear suitable protective clothing.
- Eye protection : Chemical goggles or safety glasses.
- Others: When using, do not eat, drink or smoke.

8.2. Control parameters

Occupational Exposure Limits: No data available.

VLA-ED [ppm] : 50 VLA-ED [mg/m³] : 154

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state at 20 °C : Liquid. Odour threshold : 40 ppm pH value : No data available. Melting point [°C] : -108 Decomposition point [°C] : N/A

Critical temperature [°C]: 274.6°C Auto-ignition temperature [°C]: 430

Flammability (solid, gas): Flammable liquid and vapour.

iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol) Product Code: 22393 WERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01 Page 6 of 10

Flammable.

Flash point [°C]: 27 Boiling point [°C]: 108

Initial boiling point $[^{\circ}C]$: N/A Final boiling point $[^{\circ}C]$: N/A

Evaporation rate: 0,8

Vapour pressure [20°C] : 1.2 kPa (@ 20°C) Vapour pressure mm/Hg : 9.1 (20° C)

Vapour density: 2,56 Density [g/cm3]: 0.8

Relative density, gas (air=1): 2.6 Relative density, liquid (water=1): N/A Solubility in water [% weight]: 9.5

Solubility in water: N/A

Log Pow octanol / water at 20°C : No data available.

Solubility: N/A

Viscosity at 40°C [mm2/s]: N/A

9.2. Other information Explosive properties : N/A

Explosion limits - upper [%]: 10.9 Explosion limits - lower [%]: 1.2 Oxidising properties: No data available.

10. Stability and reactivity

10.1. Reactivity

Reactivity: Not established. **10.2. Chemical stability**

Chemical stability: Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions Hazardous reactions : Not established.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Extremely high or low temperatures. Open flame.

Overheating. Heat. Sparks. **10.5. Incompatible materials**

Materials to avoid: Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products: Fumes. Carbon monoxide. Carbon dioxide.

May release flammable gases.

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 7 of 10

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity

- Inhalation : Based on available data, the classification criteria are not met.
- **Dermal**: Based on available data, the classification criteria are not met.
- **Ingestion**: Based on available data, the classification criteria are not met.

Corrosion: Causes serious eye damage.

Irritation: Causes skin irritation. May cause respiratory irritation.

Sensitization: Based on available data, the classification criteria are not met. **Mutagenicity**: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met. **Toxic for reproduction**: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met

Aspiration hazard: Based on available data, the classification criteria are not met.

12. Ecological information

12.1. Toxicity

Toxicity information: Not established.

12.2. Persistence - degradability

Persistence - degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Not established.

12.4. Mobility in soil

Mobility in soil: Not established. **Log Pow octanol / water at 20°C**: 0.7

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: The substance does not fulfil the criteria to be identified as PBT substance or vPvB substance according to Annex XIII of Regulation REACH.

12.6. Other adverse effects

Environmental precautions: Avoid release to the environment.

13. Disposal considerations

13.1. Waste treatment methods

General: Avoid release to the environment. Dispose in a safe manner in accordance with

Material Safety Data Sheet iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol) Product Code: 22393 Page 8 of 10

local/national regulations. Dispose of this material and its container to hazardous or special waste collection

point, in accordance with local, regional, national and/or international regulation.

Special precautions: Handle empty containers with care because residual vapours are flammable.

14. Transport information

14.1. Land transport (ADR-RID)

Proper shipping name: ISOBUTANOL (ISOBUTYL ALCOHOL)

UN N°: 1212 H.I. nr: 30 ADR - Class: 3

Labelling - Transport: 3: Flammable liquid.

ADR - Classification code: F1

ADR - Group : III

ADR - Packing instructions: P001 R001 LP001

ADR - Limited Quantity: 5 L

ADR - Tunnel code: D/E: Bulk or tank carriage: Passage forbidden through tunnels of category D and E. Other carriage: Passage forbidden through tunnels of category E.

14.2. Sea transport (IMDG) [English only]

Proper shipping name: ISOBUTANOL (ISOBUTYL ALCOHOL)

UN N°: 1212

IMO-IMDG - Class or division: 3: Flammable liquid.

IMO-IMDG - Packing group: III

IMO- IMDG - Packing instructions: P001 LP01

IMO-IMDG - Limited quantities : 5 L **IMO-IMDG - Marine pollution** : No

EMS-Nr: F-E S-D

14.3. Air transport (ICAO-IATA) [English only]

Proper shipping name: ISOBUTANOL (ISOBUTYL ALCOHOL)

UN N°: 1212

IATA - Class or division: 3: Flammable liquid.

IATA - Packing group : III

IATA - Passenger and Cargo Aircraft : ALLOWED

- Passenger and Cargo - Packing: 355

instruction

- Passenger and Cargo - Maximum : 60 L

Quantity/Packing

IATA - Cargo only : ALLOWED

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 9 of 10

Cargo only - Packing instruction : 366
 Cargo only - Maximum Quantity/ : 220 L

Packing

IATA - Limited Quantites: 10 L

ERG-Nr: 3L

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental: Ensure all national/local regulations are observed. **regulations/legislation specific for the substance or mixture**

REACH Restrictions - Annex XVII: The components of this product are not subject to restrictions.

REACH Authorisation - Annex XIV: The components of this product are not subject to authorization.

15.2. Chemical Safety Assessment

Chemical Safety Assessment: It has not been carried out.

16. Other information

Abbreviations and acronyms: PBT: persistent, bioaccumulative and toxic.

vPvB: very persistent and very bioaccumulative

Sources of key data used: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

Further information: None.

In accordance with REACH Regulation (CE) N° 1907/2006 and with CLP Regulation (CE) N° 1272/2008 DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document

Prepared by: MOLYCHEM (INDIA)

Material Safety Data Sheet	MOLYCHEM
iso-BUTANOL AR (iso-Butyl alcohol, 2 methyl propan-1-ol)	VERSION: 02 DATE OF ISSUE: 26-08-2019 SUPERSEDES: 01
Product Code : 22393	Page 10 of 10

For questions contact: MOLYCHEM

Office: 78/80 Babu Genu Road, Souri Bldg., 2nd Floor, Mumbai – 400 002 (INDIA)

Tel: +91 22 4066 8111, 2205 7772 . Fax: +91 22 2203 4442.

Email: info@molychem.net

Works: Plot No. B/9, Badlapur M.I.D.C., OPP. Shobhavat Textile Co.,

Kulgaon, Badlapur (E), Dist.-Thane-421 503

(The statements contained herein are offered for informational purposes only and are based upon technical data that MOLYCHEM believes to be accurate. It is intended for use only by persons having the necessary technical skills and at their own discretion and risk. Since conditions and manner of use are outside our control, we make NO WARRANTY, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE.)