

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 1 of 14

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : PETROLEUM ETHER 40-60°C AR
Product code : 32080
Identification of the product : PETROLEUM ETHER 40-60°C AR
CAS No : 8032- 32- 4
EC Index-No. : 649-263-00-9
EC No. : 232-453-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3. Details of the supplier of the safety data sheet

Company identification MOLYCHEM INDIA LLP
Office: Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)
Tel: +91 22 4066 8111, 2205 7772 .
Email : info@molychem.net
Works: Plot No. B/9, Badlapur M.I.D.C.,
OPP.Shobhavat Textile Co., Kulgaon, Badlapur (E),
Dist.-Thane-421 503.

1.4. Emergency telephone number

Emergency number : +91 22 4066 8111 (10:00am - 6:00 pm)

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Germ cell mutagenicity, Category 1B H340
Carcinogenicity, Category 1B H350
Aspiration hazard, Category 1 H304

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause cancer. May cause genetic defects. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 2 of 14

Hazard pictograms (CLP)



GHS02



GHS07



GHS09

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H340 - May cause genetic defects.
H350 - May cause cancer.

Precautionary statements (CLP)

H411 - Toxic to aquatic life with long lasting effects.
: P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P308+P313 - IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

3. Composition/information on ingredients

3.1. Substances

Name : PETROLEUM ETHER 40-60°C

CAS-No : 8032- 32- 4

4. First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 3 of 14

First-aid measures after skin contact	: Wash with plenty of water/.... Wash contaminated clothing before reuse. Get medical advice/attention. Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a POISON CENTER/doctor. Rinse mouth. Do not induce vomiting. Call a physician immediately.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause genetic defects. May cause cancer. Causes damage to organs.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Irritation
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung oedema

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam. Water spray
Unsuitable extinguishing media	: Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3 Advice for firefighters

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 4 of 14

Firefighting instructions

: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment

: Wear recommended personal protective equipment.

Emergency procedures

: Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/ personal protection"

Emergency procedures

: Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 5 of 14

Methods for cleaning up

possible.
: Take up liquid spill into absorbent material. Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Notify authorities if product enters sewers or public waters.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

7. Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures

: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately. Always wash hands after handling the product.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 6 of 14

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
- Storage conditions : Keep in fireproof place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up
- Storage away from : Open flame. Direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

7.3. Specific end use(s)

No additional information available

8. Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

- Eye protection : Chemical goggles or safety glasses
- Hand protection : Wear protective gloves
- Skin protection : Wear suitable protective clothing
- Respiratory protection : Wear appropriate mask. [In case of inadequate ventilation] wear respiratory protection.

8.2.3. Environmental exposure controls

Avoid release to the environment

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear liquid.
- Colour : Colourless.
- Odour : gasoline or kerosene.
- Odour threshold : Not available
- pH : Not available

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 7 of 14

Melting point	: Not applicable
Freezing point	: < -73 °C
Boiling point	: 40 – 60 °C
Flash point	: -45 °C
Auto-ignition temperature	: 230 °C
Decomposition temperature	: Not available
Flammability	: Flammable Highly flammable liquid and vapour.
Vapour pressure	: 40 mm Hg at 20°C
Relative vapour density at 20 °C	: 3 (Air = 1)
Relative density	: Not available
Density	: 0.65 g/cm ³ at 20 °C
Solubility	: Water: Immiscible with water
Partition coefficient n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: 0.4 mm ² /s at 25 °C

9.2. Other information

No additional information available

10. Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Open flame. Direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

11. Toxicological information

11.1. Information on toxicological effects

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 8 of 14

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Additional information	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

12. Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Ecology - water	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

13. Disposal considerations

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 9 of 14

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Disposal must be done according to official regulations
Additional information	: Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container.
Ecological waste information	: Hazardous waste due to toxicity.

14. Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1268
UN-No. (IMDG)	: UN 1268
UN-No. (IATA)	: UN 1268
UN-No. (ADN)	: UN 1268
UN-No. (RID)	: UN 1268

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IATA)	: Petroleum distillates, n.o.s.
Proper Shipping Name (ADN)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (RID)	: PETROLEUM DISTILLATES, N.O.S.
Transport document description (ADR)	: UN 1268 PETROLEUM DISTILLATES, N.O.S. (PETROLEUM ETHER 40-60 °C), 3, II, (D/E)
Transport document description (IMDG)	: UN 1268 PETROLEUM DISTILLATES, N.O.S. (PETROLEUM ETHER 40-60 °C), 3, II
Transport document description (IATA)	: UN 1268 Petroleum distillates, n.o.s. (PETROLEUM ETHER 40-60 °C), 3, II
Transport document description (ADN)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II
Transport document description (RID)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
----------------------------------	-----

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

• ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 10 of 14

Danger labels (ADR) : 3

IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3

IATA

Transport hazard class(es) (IATA) : 3

Danger labels (IATA) : 3

ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3

RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3

14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container

instructions (ADR) : T7

Portable tank and bulk container special

provisions (ADR) : TP1, TP8, TP28

Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation : S2, S20

(ADR)

Hazard identification number (Kemler No.) : 33

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 11 of 14

Tunnel restriction code (ADR) : D/E
EAC code : 3YE
Transport by sea
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP8, TP28
Stowage category (IMDG) : B
MFAG-No : 128

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3H

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28
Tank codes for RID tanks (RID) : L1.5BN
Transport category (RID) : 2

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 12 of 14

Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code Applicable on	Reference code Applicable on
3(a)	PETROLEUM ETHER 40-60°C
3(b)	PETROLEUM ETHER 40-60°C
40	PETROLEUM ETHER 40-60°C

PETROLEUM ETHER 40-60°C is not on the REACH Candidate List

PETROLEUM ETHER 40-60°C is not on the REACH Annex XIV List

Not listed on the PIC list (Regulation EU 649/2012)

Not listed on the POP list (Regulation EU 2019/1021)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Germany

Water hazard class (WGK)

: WGK 1, Slightly hazardous to water
(Classification according to AwSV; ID No. 6)

Chemicals Prohibition Ordinance (ChemVerbotsV)

: This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 13 of 14

carrying out the delivery (according to § 8 paragraph 1, 3 and 4),
identification and documentation (according to § 9 paragraph 1 to 3)
and exclusion of the shipping route (according to § 10).

Netherlands

SZW-lijst van kankerverwekkende stoffen

: PETROLEUM ETHER 40-60°C is listed

SZW-lijst van mutagene stoffen

: PETROLEUM ETHER 40-60°C is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: The substance is not listed

SZW-lijst van reprotoxische stoffen –

: The substance is not listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen –

: The substance is not listed

Ontwikkeling

Denmark

Classification remarks

: Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

16. Other information

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand
COD	Chemical oxygen demand
COD	Chemical oxygen demand
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered

Material Safety Data Sheet



PETROLEUM ETHER 40-60°C AR

VERSION : 05
REVISION DATE : 14/06/2025
EFFECTIVE DATE : 16/06/2025

Product Code : 32080

Page 14 of 14

IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties
Full text of H- and EUH-statements	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

MOLYCHEM INDIA LLP

H.Q. : Maker Tower 'E', 41-A2, 4th Floor, Above Maker Arcade, Cuffe Parade, Mumbai 400 005 (INDIA)

Tel. : +91 22 4066 8111 • Email: info@molychem.net • Web: www.molychem.net

Works : Unit I - Plot No. B/9, Unit II - Plot No. B/11, Badlapur M.I.D.C., Opp. Shobhavat Textile Co., Kulgaon, Badlapur (E), Dist.-Thane-421 503.

•ISO 9001:2015 • ISO 14001: 2015 • ISO 45001:2018 • WHO-GMP Certified • MSME Registered • CAA Registered